

HUBER+SUHNER® DATA SHEET

Sencity Rail Antenna: 1399.17.0122



Rev.: U

SWA-0859/360/4/0/V_3

Description

Railway rooftop antenna for GSM 900, GSM 1800, GSM 1900, UMTS, LTE, WiFi and WiMAX 2.4, 3.5, 5.3 and 5.8 GHz Bands. Rugged design, meets EN 50155 railway standard. Fire retardant acc. to DIN 5510-2, BS 6853, NF F16-101/102, CEN/TS 45545 (2009). Works also on non-metallic surfaces. Split installation support. Optional grounding kit available. Optional conduit support kit available to protect the cabling.



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	698 - 806	806 - 960	1710 - 2170	2400 - 2700
VSWR	1.8	1.5	1.5	1.5
Gain (dBi)	5	5	7	9.5

	Band 5	Band 6		
Frequency (MHz)	3400 - 3700	4900 - 5935		
VSWR	1.5	1.5		
Gain (dBi)	8	8		

General Data

Nominal impedance 50 Ω
DC grounded Yes
Polarisation vertical
Connector N, jack (female),
Composite power max. 100 W at ambient temperature 50 °C
Ground plane: Indicated VSWR values are valid for a metallic ground plane of 0.5 x 0.5m or larger. In the 790-5935 MHz band, Indicated VSWR values are also valid for installations on non-metallic surfaces (no specific ground plane requirements).

Mechanical Data

Dimensions (mm) 90 x 100 x 256 (Height x Width x Depth)
Weight 0.8 kg
Wind speed survival: 500km/h, operational: 500 km/h
High-current-protection: Designed acc. to UIC 533, DC-grounded antenna element (protection against lightning and short circuit with catenary lines(40kA/0.1s).
Corrosion: Low corrosion design acc. to MIL-F-14072(E).
Mounting: Shall be installed in longitudinal position to the wind/driving direction.

Environmental Data

Environmental conditions outdoor
Operation temperature (°C) -45 to 85
Storage temperature (°C) -55 to 85
Transport temperature (°C) -55 to 85
Solar radiation DIN 75220

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions

HUBER+SUHNER® DATA SHEET

Sencity Rail Antenna: 1399.17.0122

Rev.: U



RoHS 2002/95/EC	compliant
IP Rating:	IP66/68
Environmental tests:	EN 50155:2007
Flammability rating	DIN 5510-2, BS 6853, NF F16-101/102, CEN/TS 45545 (2009)

Material Data

Radome colour	RAL 7043 (dark grey)
Radome material	ASA (acrylic ester-styrene-acrylonitrile)
Back plate/base plate material	Aluminium

Related Products

- 9091.99.0235 Sencity Rail Antenna grounding kit
- 9091.99.0236 Sencity Rail conduit Support Kit
- 9091.99.0251 MIMO adapter plate for Sencity Rail antennas
- 9091.99.0252 Adapter plate for Sencity Rail antenna

If the 698-790 MHz band is used, it is recommended to mount the antenna directly on a metal roof without using any kind of mechanical adaptor between antenna and roof.

Related Documents

Mounting instruction	DOC-0000295392
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing1	DOU-00146327
Outline drawing 2	DOU-00154160
3D-model (Step)	DOC-0000334509

Additional Information

This product meets the Deutsche Bahn specifications for rolling stock equipment.

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions