

HUBER+SUHNER® DATA SHEET

Coaxial Cable: RG_142_B/U



Description

Double screened coaxial cable

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Wire	0.95 mm
Dielectric	PTFE		2.95 mm
Outer conductor	Copper, Silver plated	Braid, 97 %	3.6 mm
Outer conductor	Copper, Silver plated	Braid, 94 %	4.25 mm
Jacket	FEP	RAL 8015 - br	4.95 mm +/- 0.1
Print	HUBER+SUHNER RG 142 B/U 50 Ohm (PA no.)		

Electrical Data

Impedance	50	Ω +/- 2
Max. operating frequency	6	GHz
Capacitance	95	pF/m
Velocity of signal propagation	69	%
Signal delay	4.75	ns/m
Insulation resistance	$\geq 1 \times 10^8$	M Ω m
Min. screening effectiveness	>85	dB (up to 6 GHz)
Max. operating voltage	2.5	kV _{rms} (at sea level)
Test voltage	5	kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	6.4	kg/100 m
Min. bending radius	static	30 mm
	dynamic	74 mm

Environmental Data

Temperature range	-65 °C... + 165 °C
Installation temperature	-20 °C... + 60 °C
Flammability 2002/95/EC (RoHS)	IEC 60332-3 compliant

Ordering Information

Order as	RG_142_B/U
----------	------------

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	crimped (U9) clamped (U10) soldered —
-------------	---

HUBER+SUHNER® DATA SHEET

Coaxial Cable: RG_142_B/U



Rev.: F

Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f^{0.5})$]

Coefficients:

a=	0.3956	b=	0.0645	f _{max} =	6	p _{at} 1GHz =	407
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.3		0.24		0.073		743
	0.6		0.35		0.107		525
	0.9		0.43		0.131		429
	1.2		0.51		0.155		372
	1.5		0.58		0.177		332
	1.8		0.65		0.198		303
	2.1		0.71		0.216		281
	2.4		0.77		0.235		263
	2.7		0.82		0.250		248
	3.0		0.88		0.268		235
	3.3		0.93		0.283		224
	3.6		0.98		0.299		215
	3.9		1.03		0.314		206
	4.2		1.08		0.329		199
	4.5		1.13		0.344		192
	4.8		1.18		0.360		186
	5.1		1.22		0.372		180
	5.4		1.27		0.387		175
	5.7		1.31		0.399		170
	6.0		1.36		0.415		166

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
 www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions