

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable: SPUMA\_400

Rev.: D



### Description

PE Foam - 50 Ohm - double screened

### Technical Data

#### Construction

	Material	Detail	Diameter
Centre conductor	Aluminium / Copper	Wire	2.74 mm
Dielectric	SPE (Foamed Polyethylene)		7.24 mm
Outer conductor	Aluminum / PES	longitudinal Foil, 100 %	7.4 mm
Outer conductor	Copper, Tin plated	Braid, 71 %	8.15 mm
Jacket	PE	RAL 9005 - bk	10.25 mm +/- 0.1
Print	HUBER+SUHNER SPUMA 400 50 Ohm (PA no.)		

#### Electrical Data

Impedance	50	$\Omega$ +/- 2
Max. operating frequency	6	GHz
Capacitance	78	pF/m
Velocity of signal propagation	85	%
Signal delay	3.9	ns/m
Insulation resistance	$\geq 1 \times 10^8$	M $\Omega$ m
Min. screening effectiveness	>90	dB (up to 6 GHz)
Max. operating voltage	1.6	kV <sub>rms</sub> (at sea level)
Test voltage	2.1	kV <sub>rms</sub> (50 Hz/1 min)

#### Mechanical Data

Weight	9.4	kg/100 m
Min. bending radius	static	25 mm
	repeated (for max. 50 bendings)	100 mm

#### Environmental Data

Temperature range	-20 °C... + 60 °C	-40 °C... + 85 °C
Installation temperature	-20 °C... + 60 °C	
Halogen free	IEC 60754	
2002/95/EC (RoHS)	compliant	

#### Ordering Information

Order as	SPUMA_400
----------	-----------

#### Additional Information

##### Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Cable group	U30 7 mm / 50 Ohm
-------------	-------------------

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable: SPUMA\_400



Rev.: D

**Matrix**                      **Attenuation** [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] **and Power CW** [ formula:  $(p \cdot f^{0.5})$  ]

Coefficients:

a=	0.1241	b=	0.008	f <sub>max.</sub> =	6	p <sub>at</sub> 1GHz =	410
	<b>Frequency</b>		<b>Nom. attenuation</b>		<b>Nom. attenuation</b>		<b>Max. CW power</b>
	<b>(GHz)</b>		<b>(dB / m)</b>		<b>(dB / ft)</b>		<b>(watt)</b>
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.3		0.07		0.021		749
	0.6		0.10		0.030		529
	0.9		0.12		0.037		432
	1.2		0.15		0.046		374
	1.5		0.16		0.049		335
	1.8		0.18		0.055		306
	2.1		0.20		0.061		283
	2.4		0.21		0.064		265
	2.7		0.23		0.070		250
	3.0		0.24		0.073		237
	3.3		0.25		0.076		226
	3.6		0.26		0.079		216
	3.9		0.28		0.085		208
	4.2		0.29		0.088		200
	4.5		0.30		0.091		193
	4.8		0.31		0.094		187
	5.1		0.32		0.098		182
	5.4		0.33		0.101		176
	5.7		0.34		0.104		172
	6.0		0.35		0.107		167

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

**WAIVER!**

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Industrial**

**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**