

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable: S\_10162\_B-11



### Description

Double screened low loss coaxial cable - flame retardant - free of halogen

### Technical Data

#### Construction

	Material	Detail	Diameter
Centre conductor	Copper / Aluminum Plated	Wire	3.8 mm
Dielectric	SPE (Foamed Polyethylene)		9.9 mm
Outer conductor	Copper	longitudinal Foil, 100 %	10 mm
Outer conductor	Copper	Braid, 80 %	10.8 mm
Jacket	PE (LSFH)	RAL 9005 - bk	12.9 mm +/- 0.2
Print	HUBER+SUHNER S 10162 B-11 50 Ohm (PA no.)		

#### Electrical Data

Impedance	50 $\Omega$ +/- 2
Max. operating frequency	7.5 GHz
Capacitance	77 pF/m
Velocity of signal propagation	87 %
Signal delay	3.85 ns/m
Insulation resistance	$\geq 1 \times 10^8$ M $\Omega$ m
Min. screening effectiveness	>90 dB (up to 7.5 GHz)
Max. operating voltage	1.7 kV <sub>rms</sub> (at sea level)
Test voltage	3.4 kV <sub>rms</sub> (50 Hz/1 min)

#### Mechanical Data

Weight	15 kg/100 m
Min. bending radius	static 129 mm
	dynamic 258 mm

#### Environmental Data

Temperature range	-40 °C... + 85 °C
Installation temperature	-20 °C... + 60 °C
Flammability	IEC 60332-1
Halogen free	IEC 60754
2002/95/EC (RoHS)	compliant

#### Ordering Information

Order as S\_10162\_B-11

#### Additional Information

##### Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

#### Suitable Connectors

Cable group	crimped (S39)
	clamped (on request)
	soldered —

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable: S\_10162\_B-11



Rev.: E

**Matrix**                      **Attenuation** [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] **and Power CW** [ formula:  $(p \cdot f^{0.5})$  ]

Coefficients:

a=	0.0826	b=	0.0129	f <sub>max</sub> =	7.5	p <sub>at</sub> 1GHz =	700
	<b>Frequency</b>		<b>Nom. attenuation</b>		<b>Nom. attenuation</b>		<b>Max. CW power</b>
	<b>(GHz)</b>		<b>(dB / m)</b>		<b>(dB / ft)</b>		<b>(watt)</b>
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.4		0.06		0.018		1107
	0.8		0.08		0.024		783
	1.1		0.10		0.030		667
	1.5		0.12		0.037		572
	1.9		0.14		0.043		508
	2.3		0.15		0.046		462
	2.6		0.17		0.052		434
	3.0		0.18		0.055		404
	3.4		0.20		0.061		380
	3.8		0.21		0.064		359
	4.1		0.22		0.067		346
	4.5		0.23		0.070		330
	4.9		0.25		0.076		316
	5.3		0.26		0.079		304
	5.6		0.27		0.082		296
	6.0		0.28		0.085		286
	6.4		0.29		0.088		277
	6.8		0.30		0.091		268
	7.1		0.31		0.094		263
	7.5		0.32		0.098		256

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

**WAIVER!**

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Industrial**  
**9100 Herisau, Switzerland**  
 Phone +41 (0)71 353 41 11  
 Fax +41 (0)71 353 45 90  
 www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**