



COAXIAL CABLE CONNECTORS ONLINE DATA BASE

[New selection](#)

Item details

 Jump to [\[Mechanical data\]](#) [\[Electrical data\]](#) [\[Environmental data\]](#) [\[Material\]](#) [\[Cable types\]](#)

Item description

11_BNC-75-2-12/133_NE

Connector Description

Straight cable plug for flexible cable

Series / Pattern

 • BNC – Type / [Pattern 11](#)

Highlights



Item number

22544277

Catalogue drawing

 [11_BNC-75-2-12/133_N](#)

Related documents

 [Assembly Instruction](#)

2002/95/EC (RoHS)

 compliant

Interface Standards

IEC 60169-8; MIL-STD-348A/301; CECC 22120

Mechanical data

 Jump to [\[Top\]](#)

Cable Entry Centre Contact

soldered

Cable Entry Outer Contact

clamped

Dielectric Size

2

Electrical data

 Jump to [\[Top\]](#)

Impedance

 75 Ω

Interface Freq max

 ≤ 1 GHz

Environmental and general data

 Jump to [\[Top\]](#)

Operating Temp min

-65 °C

Operating Temp max

165 °C

Weight

0.0171 kg

Number of Matings

500

Cable Retention Force

Value considers max. load without irreversible variations of specifications

120 N

Material

 Jump to [\[Top\]](#)

2002/95/EC (RoHS)

 compliant

Piece part

Base material

Plating

Center contact

Brass

Gold Plating (Nickel underplated)

Outer contact

Brass

SUCOPLATE (R) Plating

Insulator

PFA / PTFE

Body

Brass

SUCOPLATE (R) Plating

Coupling nut

Brass

SUCOPLATE (R) Plating

Gasket

MVQ (Silicone Rubber)

Suitable cable types

 Jump to [\[Top\]](#)

Cable4

G 03133-06

Related products

 Jump to [\[Top\]](#)