

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: SF_11_N-651

Rev.: B 

Description

Straight cable plug

Interface Standards
IEC 60169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
Frequency range	DC to 18 GHz
Return loss	≥ 25 dB

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.052 kg

Environmental Data

Operating Temperature	-65 °C to 125 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)

Surface Plating

Gold Plating (without Nickel underplating)
Passivated (Plating)
Passivated (Plating)
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DCA-00044806
-----------------	--------------

Ordering Information

package	SF_11_N-651
---------	-------------

Additional Information

Suitable cable	SUCOFLEX_106
----------------	--------------

Remarks

combi nut

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions