

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_N-50-5-18/103_N



Description

Straight cable plug

Interface Standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact soldered
Outer contact soldered

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

| | |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PTFE |
| Coupling nut | Brass |
| Gasket | SI |

Surface Plating

| |
|-----------------------|
| SUCOPRO Plating |
| Silver Plating |
| Silver Plating |
| SUCOPLATE (R) Plating |

Related Documents

Outline drawing DOU-00061619
Assembly instruction DOC-0000215552

Ordering Information

Bulk 100 pcs package 11_N-50-5-18/103_NH

Additional Information

Suitable cables EZ_250_TP_M17, SM 250-01 FEP

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions