

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_QLA-01-1-8/122\_N

Rev.: A



### Description

Straight cable plug for flexible cable

Interface standards  
NIM-CAMAC-Standard CD/N549



### Technical Data

#### Electrical Data

Impedance other  $\Omega$   
Interface frequency max. 1.4 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0041 kg

#### Environmental Data

Operating Temperature -55 °C to 150 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact Brass  
Outer contact Brass  
Body Brass  
Insulator PFA / PTFE  
Crimp ferrule Copper

##### Material

##### Surface Plating

Gold Plating (Nickel underplated)  
Nickel Plating  
Nickel Plating  
SUCOPLATE (R) Plating

#### Related Documents

Catalogue drawing DOU-00006116  
Assembly instruction DOC-0000180105

#### Ordering Information

Single package 11\_QLA-01-1-8/122\_NE

#### Additional Information

Suitable cables RG\_178\_B/U, ENVIROFLEX\_178, RG\_196\_A/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**