

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_SMA-50-1-53/119_N



Description

Straight cable plug for semi-rigid cable

Interface Standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact soldered

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Coupling nut
Gasket

Material

Bronze
Stainless Steel
Stainless Steel
PFA / PTFE
Stainless Steel
MVQ (Silicone Rubber)

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

Passivated (Plating)

Related Documents

Outline drawing DOU-00008184
Assembly instruction DOC-0000183975

Ordering Information

Bulk 100 pcs package 11_SMA-50-1-53/119_NH

Additional Information

Suitable cables EZ_47_TP_M17, SUCOFORM_47_CU

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions