

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 16_N-50-7-28/133_N

Rev.: B



Description

Right angle cable plug for flexible cable

Interface standards

IEC 60169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω

Interface frequency max. 11 GHz

Mechanical Data

Centre contact crimped

Outer contact crimped

Weight 0.0642 kg

Environmental Data

Operating Temperature -65 °C to 165 °C

2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact

Outer contact

Body

Insulator

Coupling nut

Gasket

Crimp ferrule

Material

Bronze / Brass

Brass

Brass

PFA / PTFE

Brass

MVQ (Silicone Rubber)

Brass

Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00005773

Catalogue drawing DOU-00008036

Assembly instruction DOC-0000178649

Ordering Information

Single package 16_N-50-7-28/133_NE

Additional Information

Suitable cables RG_393_U, ENVIROFLEX_393, RG_225_U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions