

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_BNO-0-4-1/133\_N



### Description

Straight cable jack for flexible cable

Interface standards  
IEC 60169-22



### Technical Data

#### Electrical Data

Impedance not defined  $\Omega$   
Interface frequency max. 0.2 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0161 kg

#### Environmental Data

Operating Temperature -50 °C to 125 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium / Brass
Outer contact	Brass
Body	Brass
Insulator	ETFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)
Crimp ferrule	Copper

##### Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

#### Related Documents

Outline drawing	DOU-00008215
Catalogue drawing	DOU-00008217
Assembly instruction	DOC-0000179394

#### Ordering Information

Single package 21\_BNO-0-4-1/133\_NE

#### Additional Information

Suitable cable RG\_108A/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**