

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_N-50-10-1/133\_U



### Description

Straight cable jack

Interface Standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact plugged  
Outer contact crimped  
Weight 0.0381 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Piece Parts	Material
Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Crimp ferrule	Brass

##### Surface Plating

Centre contact	Gold Plating (without Nickel underplating)
Outer contact	SUCOPLATE (R) Plating
Body	SUCOPLATE (R) Plating
Crimp ferrule	SUCOPLATE (R) Plating

#### Related Documents

Outline drawing	DOU-00007459
Catalogue drawing	DOU-00007461
Assembly instruction	DOC-0000182194

#### Ordering Information

Bulk 50 pcs package 21\_N-50-10-1/133\_UF

#### Additional Information

Suitable cables S\_10162\_B-11, S\_10172\_B-11

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**