

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_N-50-5-52/193\_N



### Description

Straight cable plug for flexible cable

Interface standards

IEC 60169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
Frequency range	DC GHz
Return loss	≥ dB

#### Mechanical Data

Centre contact	plugged
Outer contact	clamped
Weight	0.0401 kg

#### Environmental Data

Operating Temperature	-65 °C to 165 °C
-----------------------	------------------

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Brass
Insulator	Air Dielectric - Bead - PPH

##### Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

#### Related Documents

Catalogue drawing	DOU-00007999
Assembly instruction	DOC-0000179328

#### Ordering Information

Single package	21_N-50-5-52/193_NE
----------------	---------------------

#### Additional Information

Suitable cable	EZ_250_TP_M17
----------------	---------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**