

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 23_BNT-50-0-2/103_N



Description

Straight panel receptacle jack, flange mount

Interface standards
SUHNER-BNT



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 3 GHz

Mechanical Data

Weight 0.0104 kg

Environmental Data

Operating Temperature -50 °C to 125 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Bronze / Brass
Body	Brass
Insulator	PFA / PTFE

Surface Plating

Gold Plating (Nickel underplated)
Silver Plating
SUCOPLATE (R) Plating

Related Documents

Catalogue drawing	DCA-00011537
Mounting hole	DOU-00009051

Ordering Information

Single package	23_BNT-50-0-2/103_NE
----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions