HUBER+SUHNER® DATA SHEET Coaxial Panel Connector: 23_SMA-50-0-52/199_N



Description

Straight panel receptacle jack, flange mount

Interface standards IEC 60169-15 MIL-STD-348A/310 CECC 22110



 $\begin{array}{ll} \mbox{Impedance} & \mbox{50} \ \Omega \\ \mbox{Interface frequency max.} & \mbox{18 GHz} \end{array}$

Mechanical Data

Weight 0.0026 kg

Environmental Data

Operating Temperature -65 °C to 125 °C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts Material

Centre contact Copper Beryllium Alloy
Outer contact Stainless Steel
Body Stainless Steel
Insulator PFA / PTFE

Related Documents

Outline drawing DOU-00011333 Catalogue drawing DCA-00010571

Ordering Information

Single package 23_SMA-50-0-52/199_NE

Surface Plating

Gold Plating (Nickel underplated)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

HUBER+SUHNER
HUBER+SUHNER AG

RF Technology 9100 Herisau, SwitzerlandPhone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90

www.hubersuhner.com

Document: DOC-0000189205 J Issued: 08.07.10 Uncontrolled Copy Page 1/1