

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 25\_716-50-6-2/003\_-

Rev.: B



### Description

Straight panel cable jack, flange mount

Interface Standards

IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$

Interface frequency max. 7.5 GHz

#### Mechanical Data

Centre contact plugged

Outer contact crimped

Weight 0.1092 kg

#### Environmental Data

Operating Temperature -40 °C to 80 °C

2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact

Outer contact

Body

Insulator

Crimp ferrule

##### Material

Copper Beryllium / Bronze

Brass

Brass

PE

Copper

##### Surface Plating

Silver Plating

Silver Plating

Silver Plating

SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00009394

Catalogue drawing DCA-00009396

Assembly instruction DOC-0000181728

#### Ordering Information

Bulk 20 pcs package 25\_716-50-6-2/003\_-V

#### Additional Information

Suitable cable S\_06162\_D-02

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**

**RF Technology**

**9100 Herisau, Switzerland**

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**