

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 25\_N-50-7-26/133\_N



### Description

Straight panel cable jack, flange mount

Interface Standards  
IEC 61169-16\_MIL-STD-348A/304\_CECC 22210

### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0683 kg

#### Environmental Data

Operating Temperature °C to °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

| Piece Parts    | Material               |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact  | Brass                  |
| Body           | Brass                  |
| Insulator      | PE                     |

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

#### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00009531   |
| Assembly instruction | DOC-0000179268 |
| Mounting hole        | DOU-00008795   |

#### Ordering Information

Bulk 50 pcs package 25\_N-50-7-26/133\_NF

#### Additional Information

Suitable cables S\_07262\_BD, S\_07212\_BD, SX\_07262\_BD

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

**WAIVER!**  
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**