

HUBER+SUHNER® DATA SHEET

Coaxial PCB Connector: 85_MMCX-S50-0-55/119_O

Rev.: E



Description

Straight PCB jack

Interface Standards
SUHNER-MMCX



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Board mounting type surface mount
Weight 0.0002 kg

Environmental Data

Operating Temperature -40 °C to 90 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Bronze
Outer contact	Brass
Body	LCP (Liquid crystal polymer)
Insulator	

Surface Plating

Gold Plating
Gold Plating

Related Documents

Outline drawing DOU-00080841
Mounting hole DOU-00012840

Ordering Information

Tape and Reel package 85_MMCX-S50-0-55/119_OM

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions